



photo Sanibo 5

SANIBO 5

TOILET PUMP

Bathroom sewer pumping station.

Many years of experience allowed us to produce a top quality device with an extremely broad range of application.

The main application of the device is removal of sewerage from the toilet, however use of three inlets allows to collect sewerage from, e.g. bath, washing machine and toilet. The pump is equipped with plugs allowing to cover unused inlets.

The pump can be also used in the kitchen or laundry room, with no lavatory connection. Sanibo 5 is fully automated. The pump switches on automatically after filling and switches off after the sewerage is pumped out.

Sanibo 5 pump is equipped with a basket and grinders made of stainless steel providing with the guarantee of reliability, and powerful pump motor is provided with in-built thermal protection. The device is designed according to top European standards.

APPLICATION:

Water and sewerage pumping in any place where the toilet, washbasin or shower base are installed outside the stack and riser or below the sewerage discharge level.

PARAMETERS

Head (m)	Flow (l/min)	Power supply (V)
9,5	150	230
Motor power / nominal (W)	Dimensions (cm)	Weight (kg)
600	24/29/44	7



photo Conibo

photo Wqz Conio

CONIBO

CONDENSATE PUMP

CONIBO pump is a compact device intended for condensate pumping. The device operates in a fully automatic cycle.

Upon filling of the tank, the pump turns on automatically and when the condensate is pumped out, it switches off automatically.

The pump set includes a transparent discharge hose with 3/8 inch cross section and length of 6m.

The pump can periodically pump water in temperature of 50 °C. The pump can work with water pH ranging from 2.5 - 10.

APPLICATION:

Pumping of condensate from cooling units, air conditioning units, condensing furnaces.

PARAMETERS

Head (m)	Flow (l/min)	Power supply (V)	Weight (kg)
4,5	330	230	2,2
Motor power / nominal (W)	Dimensions (cm)	Tank capacity (l)	
80	13,5/17/28	1,9	